

Quality cable cutter at low price with a wide range of application.

It has a, for a long time proven ratchet drive.

Quick blade release allows fast backout in any position.

Can be used even in confined areas

All steel parts are hardened.

One hand

Technical data

Length:	9,84 in
Width of head:	5,91 in
Weight:	1,65 lbm
CutWidth:	1,34 in
CutHeight:	1,34 in
CrossSection:	500 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	33000

Area of application : max

CU/AL Conductor sectorform	470 mcm 1,34 inØ
CU/AL Conductor multiple	360 mcm 1,34 inØ
CU/AL Conductor fine wire	470 mcm 1,34 inØ
CU/AL Conductor data cable	470 mcm 1,34 inØ



Very solid and easy to use quality cable cutter with a wide range of application.

It has got a for a long time proven, ratchet drive.

Quick blade release allows fast backout in any position.

Can be used even in confined areas

All steel parts are hardened.

One and two hand

Technical data

Length:	12,60 in
Width of head:	5,71 in
Weight:	2,20 lbm
CutWidth:	2,05 in
CutHeight:	2,05 in
CrossSection:	750 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	44000

Area of application : max

CU/AL Conductor sectorform	780 mcm 2,05 inØ
CU/AL Conductor multiple	780 mcm 2,05 inØ
CU/AL Conductor fine wire	880 mcm 2,05 inØ
CU/AL Conductor data cable	880 mcm 2,05 inØ



Very solid and easy to use quality cable cutter with a wide range of application.

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position. Can be used even in confined areas

All steel parts are hardened.

One hand

Technical data

Length:	9,84 in
Width of head:	4,33 in
Weight:	1,98 lbm
CutWidth:	1,38 in
CutHeight:	1,38 in
CrossSection:	600 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	34000

Area of application : max

CU/AL Conductor sectorform	470 mcm 1,38 inØ
CU/AL Conductor multiple	360 mcm 1,38 inØ
CU/AL Conductor fine wire	580 mcm 1,34 inØ
CU/AL Conductor data cable	580 mcm 1,34 inØ



Very solid and easy to use quality cable cutter with a wide range of application.

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

All steel parts are hardened.

Blades made out of chrome - nickel steel.

Technical data

Length:	12,80 in
Width of head:	5,71 in
Weight:	2,65 lbm
CutWidth:	2,05 in
CutHeight:	2,05 in
CrossSection:	1000 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	52000

Area of application : max

CU/AL Conductor sectorform	930 mcm 2,05 inØ
CU/AL Conductor multiple	780 mcm 2,05 inØ
CU/AL Conductor fine wire	970 mcm 2,05 inØ
CU/AL Conductor data cable	970 mcm 2,05 inØ



Available only in USA

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position.

Can be used even in confined areas.

Blades made out of chrome - nickel steel, parts are hardened.

Very solid and easy to use quality cable cutter with a wide range of application.

Technical data

Length:	10,24 in
Width of head:	4,33 in
Weight:	2,07 lbm
CutWidth:	1,77 in
CutHeight:	1,77 in
CrossSection:	600 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	45000

Area of application : max

CU/AL Conductor sectorform	mcm inØ
CU/AL Conductor multiple	mcm inØ
CU/AL Conductor fine wire	mcm inØ
CU/AL Conductor data cable	mcm inØ



Verry stable cutter, best tool-size - cut-range relation.

Spezial blade geometrie. The patentet arrangement needs allmost no service.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

Drop forged blade, suitable for harder Cu and Al conductors like Almelec.

All moving parts special hardened.

Technical data

Length:	9,84 in
Width of head:	4,33 in
Weight:	2,20 lbm
CutWidth:	1,65 in
CutHeight:	1,65 in
CrossSection:	600 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	42000

Area of application : max

CU/AL Conductor sectorform	580 mcm 1,65 inØ
CU/AL Conductor multiple	580 mcm 1,65 inØ
CU/AL Conductor fine wire	580 mcm 1,65 inØ
CU/AL Conductor data cable	580 mcm 1,65 inØ



Very solid and easy to use quality cable cutter with a wide range of application.

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

All steel parts are hardened.

Blades made out of chrome - nickel steel.

Technical data

Length:	16,14 in
Width of head:	6,30 in
Weight:	4,41 lbm
CutWidth:	2,44 in
CutHeight:	2,44 in
CrossSection:	1500 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	62000

Area of application : max

CU/AL Conductor sectorform	1460 mcm 2,44 inØ
CU/AL Conductor multiple	1460 mcm 2,44 inØ
CU/AL Conductor fine wire	1460 mcm 2,44 inØ
CU/AL Conductor data cable	1460 mcm 2,44 inØ



Very solid and easy to use reinforced cable cutter, with a wide range of application.

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

All steel parts are hardened.

Blades made out of chrome - nickel steel.

Technical data

Length:	16,14 in
Width of head:	6,30 in
Weight:	4,85 lbm
CutWidth:	2,44 in
CutHeight:	2,44 in
CrossSection:	1700 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	64000

Area of application : max

CU/AL Conductor sectorform	1460 mcm 2,44 inØ
CU/AL Conductor multiple	1460 mcm 2,44 inØ
CU/AL Conductor fine wire	1460 mcm 2,44 inØ
CU/AL Conductor data cable	1460 mcm 2,44 inØ



Very solid and easy to use professional cable cutter with a wide range of application.

It has got a for a long time proven, needle-roller bearing ratchet drive.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

All steel parts are hardened.

Blades made out of chrome - nickel steel.

Technical data

Length:	24,02 in
Width of head:	7,48 in
Weight:	6,61 lbm
CutWidth:	3,15 in
CutHeight:	3,15 in
CrossSection:	2000 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	80000

Area of application : max

CU/AL Conductor sectorform	1950 mcm 3,15 inØ
CU/AL Conductor multiple	1950 mcm 3,15 inØ
CU/AL Conductor fine wire	1950 mcm 3,15 inØ
CU/AL Conductor data cable	1950 mcm 3,15 inØ



Special cable cutter for multiple telephone or data cable.

Unsuited for sector-installations or other energy cables.

Quick blade release allows fast backout in any position. Can be used even in confined areas.

Very low friction, many times proven needle bearing drive. Smooth, clean cut.

Technical data

Length:	14,57 in
Width of head:	6,89 in
Weight:	3,31 lbm
CutWidth:	2,95 in
CutHeight:	2,95 in
CrossSection:	600 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	75000

Area of application : max

CU/AL	mcm
Conductor	inØ
sectorform	
CU/AL	mcm
Conductor	inØ
multiple	
CU/AL	mcm
Conductor	inØ
fine wire	
CU/AL	580 mcm
Conductor	2,95 inØ
data cable	



Cable shear Open C-type

Quick blade release allows fast backout in any position.
Can be used even in confined areas.

Blade with needle bearing.

Compact one - handed tool with low friction and solid technical drive, for the daily application.

Technical data

Length:	9,65 in
Width of head:	3,94 in
Weight:	1,98 lbm
CutWidth:	0,98 in
CutHeight:	0,98 in
CrossSection:	400 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	21000

Area of application : max

CU/AL Conductor sectorform	360 mcm 0,98 inØ
CU/AL Conductor multiple	360 mcm 0,98 inØ
CU/AL Conductor fine wire	360 mcm 0,98 inØ
CU/AL Conductor data cable	360 mcm 0,98 inØ



Cable shear Open C-type

Quick blade release allows fast backout in any position.

Can be used even in confined areas.

Blade with needle bearing.

One - and two - handed tool with its extended cutting area.

Technical data

Length:	12,99 in
Width of head:	5,36 in
Weight:	2,87 lbm
CutWidth:	1,42 in
CutHeight:	1,42 in
CrossSection:	500 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	23000

Area of application : max

CU/AL Conductor sectorform	470 mcm 1,42 inØ
CU/AL Conductor multiple	470 mcm 1,42 inØ
CU/AL Conductor fine wire	470 mcm 1,42 inØ
CU/AL Conductor data cable	470 mcm 1,42 inØ



Cable shear Open C-type

Cuts smooth and clean - no crushing.

Quick blade release allows fast backout in any position.

Can be used even in confined areas.

One - and two - handed cable cutter with needle bearing drive, very low friction.

Blade and ratched drive with needle bearing.

Technical data

Length:	12,99 in
Width of head:	5,36 in
Weight:	3,09 lbm
CutWidth:	1,42 in
CutHeight:	1,42 in
CrossSection:	600 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	25000

Area of application : max

CU/AL Conductor sectorform	580 mcm 1,42 inØ
CU/AL Conductor multiple	580 mcm 1,42 inØ
CU/AL Conductor fine wire	580 mcm 1,42 inØ
CU/AL Conductor data cable	580 mcm 1,42 inØ



Cable shear Open C-type

Cuts also very fine wires like welder cable without deformation.

Quick blade release allows fast backout in any position.

Can be used even in confined areas.

Blade and ratched drive with needle bearing.

Biggest version, this tool separates also cable with thin sheet metal coating.

Technical data

Length:	19,09 in
Width of head:	7,68 in
Weight:	6,61 lbm
CutWidth:	2,17 in
CutHeight:	2,17 in
CrossSection:	1000 mcm
Handles:	Polypropylen
Surface:	brown-finished
OrderNumber:	27000

Area of application : max

CU/AL Conductor sectorform	1070 mcm 2,17 inØ
CU/AL Conductor multiple	1070 mcm 2,17 inØ
CU/AL Conductor fine wire	1070 mcm 2,17 inØ
CU/AL Conductor data cable	1070 mcm 2,17 inØ

